



## ASPIRATEUR INDUSTRIEL pour le nettoyage, l'aspiration et l'optimisation de vos opérations de maintenance



-Cet aspirateur industriel est puissant, robuste et silencieux. Il est équipé de trois unités d'aspiration insonorisées et auto-refroidies à haute puissance (« by-pass »).

Le KMB3.070 est l'outil idéal pour l'aspiration de déchets légers, y compris colmatants. Son filtre étoile hygiénique, doté d'une grande surface de filtration, garantit une efficacité d'aspiration maximale lors de la collecte de vos poussières fines.

Sa conception robuste garantit une fiabilité à long terme, grâce à son châssis renforcé, ses roues de grand diamètre et sa cuve sur roulettes.

Puissance	3 KW
Tension	230   50/60 V
Dépression maximal	2.100 mmH <sup>2</sup> O
Débit d'aire maximum	520 m <sup>3</sup> /h
Capacité de la cuve	120 l



Bouton ON/OFF



Châssis robuste avec roues de grand diamètres et freins



Filtre à cartouche

# KMB3.070



## GENERAL FEATURES

- Draining valve and expelling system
- Liquids bin level monitoring system switch off

## TECHNICAL DATA

		50/60 Hz
<b>Power</b>	kW - HP	3 - 4
<b>Input voltages Y <sup>1)</sup></b>	V	230
<b>Current Y</b>	A	13,5
<b>Electric protection <sup>a)</sup></b>		IP43
<b>Default factory setting</b>	V   Hz	230   50/60
<b>Electrical cable:</b>		
type		3G1,5 H07RN-F
length	m	9
plug		Schuko
<b>Insulation class <sup>b)</sup></b>		F
<b>Maximum vacuum</b>	mmH <sub>2</sub> O	2.100
	mbar	210
<b>Maximum air flow</b>	l/min	8.667
	m <sup>3</sup> /h	520
<b>Acoustic level <sup>c)</sup></b>	dB (A)	73
<b>Environmental working temperature</b>	°C	5 ÷ 40
<b>Dust bin capacity</b>	l	120
<b>Wheels material</b>		Rubber
<b>Weight</b>	kg	89
<b>Packing weight</b>	kg	99
<b>Dimensions - L x W x H</b>	mm	705 x 603 x 1.410
<b>Standard packing size - L x W x H</b>	mm	740 x 730 x 1.610
<b>Diameters:</b>		
material inlet	mm	70
draining valve	mm	3/4"
wheels: rear   front	mm	150 - 200
wheels: bin	mm	60

## FILTRATION DATA

• Default primary filter		Cartridge filters	
Surface area	cm <sup>2</sup> - m <sup>2</sup>	21.000 - 2,1	
Diameter	mm	460	
Dust Class <sup>d)</sup>   Media <sup>3)</sup>		---   Polyester - oil & water repellent	

## EXPELLING SYSTEM

	Pump power	kW - HP	0,75 - 1,01
	Pump capacity	l/min	220
	Hose length   inner diameter	m   mm	3   30

## SWARF BASKET

	Capacity	l	40	
	Diameter	basket	mm	450
		holes	mm	2

Normatives: a) IEC60529; b) IEC600085; c) EN60704-2-1; d) EN60335-2-69;

Notes:

<sup>1)</sup> Other input voltages upon request

<sup>2)</sup> Maximum vacuum in continuous run

<sup>3)</sup> Other materials available according to the material to be vacuumed

## MACHINE

<b>KMB3.070</b>	3 kW, blue RAL 5012 painted, 460 mm diameter single phase industrial sumps cleaner
<b>KMB3.070-60Hz</b>	3 kW, blue RAL 5012 painted, 460 mm diameter single phase industrial sumps cleaner

## OUTFITS

<b>001</b>	AISI 304 stainless steel dust bin	
<b>002</b>	AISI 304 stainless steel dust bin and filtering chamber	
<b>003</b>	Entirely made out of AISI 304 stainless steel	
<b>320</b>	Vulkollan wheels	
<b>MARKWH</b>	Mark proof wheels with bearings	