

ASPIRATEUR INDUSTRIEL pour PROCESS

Les aspirateurs de la gamme KV sont des aspirateurs polyvalents, adaptés à l'aspiration de tous types de poussières.

Ces aspirateurs sont insonorisés et équipés d'une unité aspirante triphasée sans entretien, permettant une aspiration 24 h/24.

Les KV1636.F240 sont également dotés de filtres hygiéniques de grande surface et sont déclinables en version ATEX afin de travailler dans des atmosphères explosives.

Les principales applications des aspirateurs KV sont : les machines d'usinage de précision et d'assemblage, les machines de conditionnement, ainsi que les secteurs de la production alimentaire, cosmétique et pharmaceutique.



Puissance	1,5 KW
Tension	400 V 50 Hz
Dépression maximal	2.800 mmH ² O
Débit d'air maximum	230 m ³ /h
Capacité de la cuve	25 l



Poignée de décolmatage



Filtre étoile



Option : Filtre absolu en amont (HEPA) avec filtre M

KV1636.F240





GENERAL FEATURES

- Overheating safety relief valve
- L-M-H filtration for hazardous dust vacuuming upon request

TECHNICAL DATA

		50 Hz	60 Hz
Power	kW - HP	1,5 - 2,0	1,7 - 2,3
Input voltages Y ¹⁾	V	400	460
Current Y	A	3,2	3,07
Input voltages D ¹⁾	V	230	265
Current D	A	5,54	5,32
Electric protection ^{a)}		IP55	
Default factory setting	V Hz	400 50	
Electrical cable:			
type		4G1,5 H07RN-F	
length	m	6	
plug		Not supplied	
Insulation class ^{b)}		F	
Energetic class ^{d)}		IE3	
Maximum vacuum	mmH ₂ O	2.800	3.500
	mbar	280	350
Nominal vacuum ²⁾	mmH ₂ O	1.750	1.600
	mbar	175	160
Maximum air flow	l/min	3.833	4.633
	m ³ /h	230	278
Acoustic level ^{d)}	dB (A)	69	0
Environmental working temperature	°C	5 ÷ 40	
Dust bin capacity	l	25	
Weight	kg	55	
Packing weight	kg	75	
Dimensions - L x W x H	mm	540 x 460 x 1.240	
Packing size - L x W x H	mm	820 x 550 x 1.630	
Diameters:			
material inlet	mm	50	
air exhaust	mm	80	

FILTRATION DATA

	Primary star filter	Default	Variant 120M16
	Dust Class ^{d)}	L	M
	Media ²⁾	Polyester	Polyurethane injected polyester
	Surface area	cm ² - m ²	7.000 - 0,7
	Diameter	mm	360
	Filter cleaning type	Manual filter shaker	
	Upstream absolute filter - Variant 005		
	Surface area	cm ² - m ²	16.000 - 1,6
	Media	Glass fibre	
	Dust Class ^{e)}	H14	
	Efficiency M.P.P.S. ^{e) 3)}	99,995%	

Normatives: a) IEC60529; b) IEC600085; c) EN60704-2-1; d) EN60335-2-69; e) EN1822

Notes:

- ¹⁾ Other input voltages upon request
²⁾ Maximum vacuum in continuous run
³⁾ Other materials available according to the material to be vacuumed
⁴⁾ With 0,18 µm particles
⁵⁾ "Pharma finishing": AISI 316L cleaned welding and inner mirror polished

MACHINE

KV1636.F240	1,5 kW, 25 l capacity, grey RAL 9006 painted, 360 mm diameter three phase industrial vacuum cleaner
KV1636.F240-60Hz	1,7 kW, 25 l capacity, grey RAL 9006 painted, 360 mm diameter three phase industrial vacuum cleaner

OUTFITS

ACD	Appliance for combustible dust vacuuming according to IEC 60335-2-69 ED6 – 2020
001	AISI 304 stainless steel dust bin
001P	AISI 316L stainless steel dust bin - Pharma finishing ⁵⁾
003	Entirely made out of AISI 304 stainless steel
003P	AISI 304 stainless steel completely made with AISI 316L stainless steel dust bin and filtering chamber - Pharma finishing ⁵⁾
005	Upstream absolute filter (HEPA) with M dust class primary filter
090	On/off switch with thermal protection
100	Single phase vacuum unit with capacitor
104	Remote on/off switch arrangement through dry contact onto processing machine electric control panel
120	M dust class primary filter
120M16	M dust class high surface primary filter
435	Silencer for painted versions
961	Chassis with wheels
SILINOX	Silencer for stainless steel versions