



ASPIRATEUR INDUSTRIEL pour le nettoyage, l'aspiration et l'optimisation de vos opérations de maintenance



Cet aspirateur industriel est puissant, robuste et silencieux. Il est équipé de trois unités d'aspiration insonorisées et auto-refroidies à haute puissance.

Le KMB3.070 est l'outil idéal pour l'aspiration des lubrifiants, huiles et copeaux. Son filtre à cartouche garantit une efficacité d'aspiration maximale lors de la collecte de vos déchets.

Équipé d'un voyant de trop-plein et d'un interrupteur de vidange, il rend vos opérations de maintenance simples et efficaces.

Sa conception robuste assure une fiabilité à long terme, grâce à son châssis renforcé, ses roues de grand diamètre et sa cuve montée sur roulettes.

Puissance	3 KW
Tension	230 V 50/60 Hz
Dépression maximal	2.100 mmH ² O
Débit d'air maximum	520 m ³ /h
Capacité de la cuve	120 l



Bouton ON/OFF



Châssis robuste avec roues de grand diamètres et freins



Filtre à cartouche

KMB3.070



GENERAL FEATURES

- Draining valve and expelling system
- Liquids bin level monitoring system switch off

TECHNICAL DATA

		50/60 Hz
Power	kW - HP	3 - 4
Input voltages Y ¹⁾	V	230
Current Y	A	13,5
Electric protection ^{a)}		IP43
Default factory setting	V Hz	230 50/60
Electrical cable:		
type		3G1,5 H07RN-F
length	m	9
plug		Schuko
Insulation class ^{b)}		F
Maximum vacuum	mmH ₂ O	2.100
	mbar	210
Maximum air flow	l/min	8.667
	m ³ /h	520
Acoustic level ^{c)}	dB (A)	73
Environmental working temperature	°C	5 ÷ 40
Dust bin capacity	l	120
Wheels material		Rubber
Weight	kg	89
Packing weight	kg	99
Dimensions - L x W x H	mm	705 x 603 x 1.410
Standard packing size - L x W x H	mm	740 x 730 x 1.610
Diameters:		
material inlet	mm	70
draining valve	mm	3/4"
wheels: rear front	mm	150 - 200
wheels: bin	mm	60

FILTRATION DATA

• Default primary filter		Cartridge filters	
	Surface area	cm ² - m ²	21.000 - 2,1
	Diameter	mm	460
	Dust Class ^{d)} Media ³⁾		--- Polyester - oil & water repellent

EXPELLING SYSTEM

	Pump power	kW - HP	0,75 - 1,01
	Pump capacity	l/min	220
	Hose length inner diameter	m mm	3 30

SWARF BASKET

	Capacity	l	40	
	Diameter	basket	mm	450
		holes	mm	2

Normatives: a) IEC60529; b) IEC600085; c) EN60704-2-1; d) EN60335-2-69;

Notes:

¹⁾ Other input voltages upon request

²⁾ Maximum vacuum in continuous run

³⁾ Other materials available according to the material to be vacuumed

MACHINE

KMB3.070 3 kW, blue RAL 5012 painted, 460 mm diameter single phase industrial sumps cleaner

KMB3.070-60Hz 3 kW, blue RAL 5012 painted, 460 mm diameter single phase industrial sumps cleaner

OUTFITS

001	AISI 304 stainless steel dust bin	
002	AISI 304 stainless steel dust bin and filtering chamber	
003	Entirely made out of AISI 304 stainless steel	
320	Vulkollan wheels	
MARKWH	Mark proof wheels with bearings	