

ASPIRATEUR INDUSTRIEL pour PROCESS

Les aspirateurs de la gamme KF sont des aspirateurs polyvalents, adaptés à l'aspiration de tous types de poussières.

Ces aspirateurs sont insonorisés et équipés d'une unité aspirante triphasée sans entretien, permettant une aspiration 24 h/24.

Les KF16M.Z2 sont également dotés de filtres hygiéniques de grande surface et sont déclinables en version ATEX afin de travailler dans des atmosphères explosives.

Les principales applications des aspirateurs KF sont : les machines d'usinage de précision et d'assemblage, les machines de conditionnement, ainsi que les secteurs de la production alimentaire, cosmétique et pharmaceutique.



Puissance	2,2 KW
Tension	400 V 50 Hz
Dépression maximal	2.500 mmH ² O
Débit d'air maximum	221 m ³ /h
Capacité de la cuve	25 l



Indicateur de colmatage



Système de décolmatage ergonomique



OPTION : Bras d'aspiration



Option : Filtre absolu en amont (HEPA) avec filtre M

KF16M.Z2



ATEX ZONES 22, 2
NO CONDUCTIVE DUST



GENERAL FEATURES

- Overheating safety relief valve
- Antistatic wheels
- H filtration for hazardous dust vacuuming upon request

TECHNICAL DATA

		50 Hz	60 Hz
Power	kW - HP	2,2 - 2,95	2,55 - 3,42
Input voltages Y ¹⁾	V	400	460
Current Y	A	4,2	4,2
Input voltages D ¹⁾	V	230	---
Current D	A	---	---
Electric protection ^{a)}		IP55	
Default factory setting	V Hz	400 50	
Electrical cable:			
type		4G1,5 H07RN-F	
length	m	6	
plug		Not supplied	
Insulation class ^{b)}		F	
Energetic class ^{c)}		IE3	
ATEX Mark ^{d)}		II3GD Ex dc h IIB T3 Gc - h tc IIIB T 125°C Dc	
Maximum vacuum	mmH ₂ O	2.500	3.000
	mbar	250	300
Nominal vacuum ²⁾	mmH ₂ O	2.200	2.400
	mbar	220	240
Maximum air flow	l/min	3.683	4.417
	m ³ /h	221	265
Acoustic level ^{e)}	dB (A)	64	70
Environmental working temperature	°C	5 ÷ 40	
Dust bin capacity	l	25	
Wheels material		Rubber	
Weight	kg	98	
Packing weight	kg	113	
Dimensions - L x W x H	mm	690 x 465 x 1.475	
Packing size - L x W x H	mm	820 x 550 x 1.630	
Diameters:			
material inlet	mm	50	
air exhaust	mm	100	
wheels: chassis	mm	100 - 150	

FILTRATION DATA

Default primary star filter		
Surface area	cm ² - m ²	7.000 - 0,7
Diameter	mm	360
Dust Class ^{f)} Media ³⁾		M Antistatic polyester
Filter cleaning		Ergonomic manual filter shaker
Upstream absolute filter - Variant 005		
Surface area	cm ² - m ²	16.000 - 1,6
Media		Glass fibre
Dust Class ^{g)}		H14
Efficiency M.P.P.S. ^{g) 4)}		99,995%
Downstream absolute filter - Variant 045		
Surface area	cm ² - m ²	55.000 - 5,5
Media		Glass fibre
Dust Class ^{g)}		H14
Efficiency M.P.P.S. ^{g) 4)}		99,995%

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) 2014/34/UE; e) EN60704-2-1; f) EN60335-2-69; g) EN1822

Notes:

¹⁾ Other input voltages upon request

²⁾ Maximum vacuum in continuous run

³⁾ Other materials available according to the material to be vacuumed

⁴⁾ With 0,18 µm particles

⁵⁾ "Pharma finishing": AISI 316L cleaned welding and inner mirror polished

MACHINE

KF16M.Z2	2,2 kW, 25 l capacity, grey RAL 9006 painted, 360 mm diameter three phase industrial vacuum cleaner
KF16M.Z2-60Hz	2,55 kW, 25 l capacity, grey RAL 9006 painted, 360 mm diameter three phase industrial vacuum cleaner

OUTFITS

001	AISI 304 stainless steel dust bin	I
001P	AISI 316L stainless steel dust bin - Pharma finishing ⁵⁾	
002	AISI 304 stainless steel dust bin and filtering chamber	I
002P	AISI 316L stainless steel dust bin and filtering chamber - Pharma finishing ⁵⁾	
003	Entirely made out of AISI 304 stainless steel	
003P	AISI 304 stainless steel completely made with AISI 316L stainless steel dust bin and filtering chamber - Pharma finishing ⁵⁾	
005	Upstream absolute filter (HEPA)	
007	Pneumatic filter shaker with push-button	
007A	Automatic pneumatic filter shaker (adjustable at switch on or at switch off)	
045	Downstream absolute filter (HEPA) - version: painted	
045SS	Downstream absolute filter (HEPA) - version: AISI 304 stainless steel	
066	Bin overfilling machine switch off	
104	Remote on/off switch arrangement through dry contact onto processing machine electric control panel	
603	Disposal bag vacuum balance system for dust collection directly into plastic bags	