

ASPIRATEUR INDUSTRIEL TRIPHASES AVEC CUVE DE 175 LITRES

Les aspirateurs industriels triphasés K560.022B, puissants et robustes, sont conçus pour les tâches les plus exigeantes dans les environnements industriels.

Les K15M.022B sont équipés d'une puissante unité aspirante triphasée de 15 kW, garantissant une aspiration efficace et rapide des débris, des poussières fines et des particules dans les environnements industriels les plus exigeants.

Les roues en polyuréthane des K560 ATEX offrent une manœuvrabilité supérieure, permettant de les déplacer facilement dans les espaces industriels encombrés.

Grâce à leur conception robuste, ces aspirateurs peuvent résister aux rigueurs des environnements de travail les plus difficiles, garantissant une durabilité à long terme.



Puissance	15,0 KW
Tension	400 V / 50 Hz
Dépression maximal	4.750 mmH ² O
Débit d'air maximum	1.260 m ³ /h
Capacité de la cuve	175 - 90 l



Indicateur de colmatage



Poignée de
décolmatage



Filtre étoile



OPTION : Cuve et Chambre
filtrante en INOX

K15/78M.022B



ATEX ZONE 22
NO CONDUCTIVE DUST



GENERAL FEATURES

- Overheating safety relief valve
- Antistatic wheels
- H filtration for hazardous dust vacuuming upon request

TECHNICAL DATA

		50 Hz	60 Hz
Power	kW - HP	15,0 - 20,45	17,3 - 23,59
Input voltages Y ¹⁾	V	---	---
Current Y	A	---	---
Input voltages D ¹⁾	V	345 ... 415	380 ... 480
Current D	A	33,2	33,9
Electric protection ^{a)}		IP55	
Default factory setting	V Hz	400 50	
Electrical cable:			
type		4G10 H07RN-F	
length	m	9 m	
plug		Not supplied	
Insulation class ^{b)}		F	
Energetic class ^{c)}		IE1	
ATEX Mark ^{d)}		II3D - Ex h tc IIIB T 135°C Dc	
Maximum vacuum	mmH ₂ O	4.750	6.000
	mbar	475	600
Nominal vacuum ²⁾	mmH ₂ O	3.150	2.450
	mbar	315	245
Maximum air flow	l/min	21.000	25.383
	m ³ /h	1.260	1.523
Acoustic level ^{e)}	dB (A)	78	79
Environmental working temperature	°C	5 ÷ 40	
Dust bin capacity	l	175 - 90	
Wheels material		Polyurethane	
Weight	kg	446	
Packing weight	kg	466	
Dimensions - L x W x H (005 - 008)	mm	1.720 x 880 x 2.165 (2.365 - 2.220)	
Standard packing size - L x W x H (005 - 008)	mm	1.800 x 950 x 2.305 (2.505 - 2.360)	
Diameters:			
material inlet	mm	100	
air exhaust	mm	150	
wheels: chassis	mm	200 - 250	
wheels: bin	mm	100	

FILTRATION DATA

	Default primary star filter	
	Surface area	cm ² - m ² 65.000 - 6,5
	Diameter	mm 780
	Dust Class ^{f)} Media ³⁾	M Antistatic polyester
	Filter cleaning	Electric filter shaker with push-button
	Optional primary filter - cartridges kit - Variant 008	
	Surface area Diameter	cm ² - m ² mm 126.400 - 12,64 780
	Dust Class ^{f)} Media	M Antistatic polyester
	Compressed air consumption pressure	nl/min bar 48 4 ÷ 6
	Filter cleaning	Automatic cleaning system
	Upstream absolute filter - Variant 005	
	Surface area	cm ² - m ² 130.000 - 13
	Media	Glass fibre
	Dust Class ^{g)}	H14
	Efficiency M.P.P.S. ^{g) 4)}	99,995%

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) 2014/34/UE; e) EN60704-2-1; f) EN60335-2-69; g) EN1822

Notes:

¹⁾ Other input voltages upon request

²⁾ Maximum vacuum in continuous run

³⁾ Other materials available according to the material to be vacuumed

⁴⁾ With 0,18 µm particles

MACHINE

K15/78M.022B	15 kW, 175 l capacity, blue RAL 5012 painted, 780 mm diameter three phase industrial vacuum cleaner
K15/78M.022B-60Hz	17,3 kW, 175 l capacity, blue RAL 5012 painted, 780 mm diameter three phase industrial vacuum cleaner
K15/78/90M.022B	15 kW, 90 l capacity, blue RAL 5012 painted, 780 mm diameter three phase industrial vacuum cleaner
K15/78/90M.022B-60Hz	17,3 kW, 90 l capacity, blue RAL 5012 painted, 780 mm diameter three phase industrial vacuum cleaner

OUTFITS

001	AISI 304 stainless steel dust bin
002	AISI 304 stainless steel dust bin and filtering chamber
003	Entirely made out of AISI 304 stainless steel
005	Upstream absolute filter (HEPA)
005SS	Upstream absolute filter (HEPA) - version: AISI 304 stainless steel
006	Electric filter shaker with push-button
006A	Automatic electric filter shaker
008	Automatic reverse jet cartridge filtering system
008SS	Automatic reverse jet cartridge filtering system - version: AISI 304 stainless steel
066	Bin overfilling machine switch off
104	Remote on/off switch arrangement through dry contact onto processing machine electric control panel
603	Disposal bag vacuum balance system for dust collection directly into plastic bags
806	Reinforced dust bin
820	Forklift forks sockets
821	Air exhaust hose fitting